12~24VDC

## SQ4-R65







## **FEATURES**

- ECE R65 certified high power output.
- ECE R10 EMC Compliance.
- High-Intensity LED x 4.
- Multi-Voltage Input 11~30VDC.
- Built-in 5 Selectable Flash Patterns.
- Long Life LEDs rated to 100,000 hours of operation.
- Non-volatile memory recalling last flash pattern used at power up.
- Multiple units synchronization in simultaneous or alternating flash.
- Reverse polarity protection.
- Weatherproof and vibration resistant design for external or internal use.
- Solid Aluminum base for efficient heat dissipation.

## **SPECIFICATIONS**

Meets: ECE R65 (XA1), ECE R10

Bulb: 1W LED x 4pcs

Warning Patterns: 5 Flash Patterns
Operating Voltage: 12~24VDC

Avg. Current: 0.32A @12VDC / 0.16A @24VDC

(varies with flash pattern)

**Avg. Power:** 3.85 Watts (varies with flash pattern) **Max. Current:** 0.64A @12VDC / 0.32A @24VDC

Max. Power: 7.7 Watts

Cable Length: 120cm (4 ft)

Wire Functions: Red - Vcc

Black - GND

Yellow - Flash Patterns & Sync & Phase

White - Steady Burn

Fuse Recommend: 1A Available in: AMBER

## **DIMENSIONS**



